

APPLICATION

Ideal for sanitary ware connections. A quick, reliable alternative to piping sanitary ware in solid pipe. If installed correctly, they absorb lateral movements arising from thermal expansion or contraction, vibration and pipe misalignment.



SPECIFICATION

Working Pressure:	10-15mm 15 Bar, 20-25mm 10 Bar
Working Temperature:	85°C
Size Range:	DN10-25
Connections:	Fixed BSPT Male Swivel Female Flat Face, complete with washer
Length:	Standard 300mm, longer lengths available on request
Features:	<ul style="list-style-type: none"> • Extra smooth bore • Class 'O' Lagging & End Caps • Tested to 1.5 times the working pressure • Threads BS21/DIN2999 • Wide selections of connections, e.g. conical faces, brass/ mild steel plated or stainless steel adapters to make a full union
Material:	<ul style="list-style-type: none"> • EPDM rubber cored with single stainless steel braid covering 95% of the rubber tube • Stainless steel ferrules • End fittings nickel-plated brass • Insulation closed cell polyurethane "Class O"



INSTALLATION

It is important that all flexible hoses are installed correctly. The hoses should not be misaligned, buckled, kinked, or be subjected to torsion.

PRODUCT CODES AND SELECTIONS

Product Code	Description	Ø[mm]	Length [mm]
SL22-010	1/4" BSPT male threaded EPDM stainless steel braided hose, swivel female flat face	10	300
SL22-015	1/2" BSPT male threaded EPDM stainless steel braided hose, swivel female flat face	15	300
SL22-020	3/4" BSPT male threaded insulated EPDM stainless steel braided hose, swivel female flat face	20	300
SL22-025	1" BSPT male threaded insulated EPDM stainless steel braided hose, swivel female flat face	25	300
SL22-xxx-01	BSPT male threaded EPDM stainless steel braided hose, swivel female flat face	xx	450
SL22-xxx-02	BSPT male threaded EPDM stainless steel braided hose, swivel female flat face	xx	600
SL22-xxx-03	BSPT male threaded EPDM stainless steel braided hose, copper compression	xx	300
SL22-xxx-04	BSPT male threaded EPDM stainless steel braided hose, copper compression	xx	450
SL22-xxx-05	BSPT male threaded EPDM stainless steel braided hose, copper compression	xx	600
SL23-xxx-xxx	Hose supplied with insulation	xx	xxx

