

APPLICATION

A quick, reliable alternative to piping up to the Fan Coil in solid pipe. If installed correctly, they absorb lateral movements arising from thermal expansion or contraction, vibration and pipe misalignment.

SPECIFICATION

Working Pressure:	½" – 15 Bar; ¾" – 10 Bar		
Working Temperature:	85°C		
Size Range:	DN15-20		
Connections:	System: ½" or ¾" BSPT Male Valve Set: 20 Euroconus		
Features:	 BSRIA tested and certified Can be supplied with isolation ball valve Suit FloSet[®] FCU valve sets 		
Material:	 EPDM rubber cored with single stainless steel braid covering 95% of the rubber tube Stainless steel ferrules End fittings nickel-plated brass Insulation closed cell polyurethane "Class 0" 		

INSTALLATION

It is important that all flexible hoses are installed correctly. The hoses should not be misaligned, buckled, kinked, or be subjected to torsion.

PRODUCT CODES AND SELECTIONS

Product Code	Description	Ø [mm]	Length [mm]
12.UF.300	½" BSPT male threaded EPDM stainless steel braided hose	15	300
12.UF.450	½" BSPT male threaded EPDM stainless steel braided hose	15	450
12.IF.300	1/2" BSPT male threaded insulated EPDM stainless steel braided hose	15	300
12.IF.450	½" BSPT male threaded insulated EPDM stainless steel braided hose	15	450
34.UF.300	¾" BSPT male threaded EPDM stainless steel braided hose	20	300
34.UF.450	¾" BSPT male threaded EPDM stainless steel braided hose	20	450
34.IF.300	³ /4" BSPT male threaded insulated EPDM stainless steel braided hose	20	300
34.IF.450	%" BSPT male threaded insulated EPDM stainless steel braided hose	20	450
12.UF.300.BV	½" BSPT female threaded ball valve with EPDM stainless steel braided hose	15	300
12.UF.450.BV	½" BSPT female threaded ball valve with EPDM stainless steel braided hose	15	450
12.IF.300.EBV	2/2" BSPT female threaded extended lever ball valve with EPDM stainless steel braided hose	15	300
12.IF.450.EBV	22" BSPT female threaded extended lever ball valve with EPDM stainless steel braided hose	15	450
34.UF.300.BV	³ /4" BSPT female threaded ball valve with EPDM stainless steel braided hose	20	300
34.UF.450.BV	%" BSPT female threaded ball valve with EPDM stainless steel braided hose	20	450
34.IF.300.EBV	³ /4" BSPT female threaded extended lever ball valve with EPDM stainless steel braided hose	20	300
34.IF.450.EBV	³ /4" BSPT female threaded extended lever ball valve with EPDM stainless steel braided hose	20	450





