FlowCon Actuators Selection Matrix

		FlowCon valve types													
	FlowCon Part no.	Green. 0/1/1HF/2	GreEQ	Green.3	SM		UniQ®	FIT-G		FIT	ADP	EVS	Unimizer®		T-JUST
	mm	15-32	15-32	40-50	15-40	50-250	15-20	15-32	40-50	15-250	15-25	15-25	15-80	100-150	15-25
Thermal ON/OFF															
24V	EV.0.4						X					X			X
	FT.0.4	X									X				
120V	EV.0.5						X					X			
230V	EV.0.3						X					X			X
	EVP.0.3						X					X			
	FT.0.3	X									X				
Thermal ON/OFF with end switch															
24V	EV.1.4						X					X			
230V	EV.1.3						X					X			
Thermal modulating															
24V	EV.0.2						X					X			
	FT.0.2	X													
Electrical 2-position															
24V	BT000S												X		
	FH			X											
	FH.1 w/failsafe			X											
	FN.0.4	X													
	FN.1.4 w/failsafe	X													
	FN.5.4						X								
	TT000													X	
230V	BT200												X		
	FNR.0.3	X													
	TT300													X	
Electrical 2-position with end switches															
24V	BT020S												X		
	TT020													X	
230V	BT220												X		
	TT320													X	
Electrical 3-point floating															
24V	BT000S												X		
	FH			X											
	FN.0.4	X													
	FN.1.4 w/failsafe	X													
	FN.5.4						X								
	TT000													X	
230V	BT200												X		
	FNR.0.3	X													
	TT300													X	
Electrical 3-point floating with end switches															
24V	BT020S												X		
	TT020													X	
230V	BT220												X		
	TT320													X	
Electrical modulating															
24V	BM000S												X		
	FNP.0.2	X													
	FNR.0.2	X	X				X								
	FNR.0.2-EQ	X													
	TM000													X	
Electrical modulating with end switches															
24V	BM020S												X		
	TM020													X	
Electrical modulating with feed-back signal															
24V 0(2)-10V	FH			X					X						
	FH BACnet/Modbus			X											
	FH.1 w/failsafe			X					X						
	FN.0.2	X						X							
	FN.0.2 BACnet/Modbus	X	X												
	FNJ.1.2 w/failsafe	X	X												
	FNJ.1.2-EQ w/failsafe	X													
24V 0(2)-10V, 0(4)-20mA or 3-point floating	SM0001				X										
24V 0(2)-10V, 0(4)-20mA, 2-position or 3-point floating	SM0003				X	X				X					
	SM0004 w/failsafe				X	X				X					
	SM0006 BACnet w/failsafe				X	X				X					
Adaptor ring for thermal actuator															
Color of ring		Black					Black				Black	Black			Red

Updated 01.2023